



ABC NEXTGEN INSPECTION CHECKLIST

Driver Name	Date	Car #	Track
Tech Inspector (signed)		Team Representative (signed)	

		(Circle One)	Fix	Penalty	
BODY REQUIREMENTS	1- NOSE	Nose Screen- Mounted flush on lower air dam in the recess provided	pass / fail	☐	
		Minimum height from ground: 4"	pass / fail	☐	
		No holes allowed above the bumper line	pass / fail	☐	
		Measured along the contour of the nose from bottom of nose to hood seam: 23 5/8" minimum	pass / fail	☐	
	2- ROOF	Air intake Opening, Maximum: 2.5" x 20"	pass / fail	☐	
		Windshield Braces- Minimum 3 required	pass / fail	☐	
		Rear Window Braces- Minimum 3 required	pass / fail	☐	
	3- DOOR VENT WINDOWS	Must be 12" length along top of door	pass / fail	☐	
		90 Degrees from top of door to A Pillar	pass / fail	☐	
		Maximum deflection of 1" Outward. Inward deflection is not allowed.	pass / fail	☐	
	4- ROCKER PANEL HEIGHT	Minimum from ground to bottom of rocker: 4"	pass / fail	☐	
	5- WHEEL OPENING	7-1/2" Max from edge of rim to rear wheel opening	pass / fail	☐	
	6- SPOILER	Max Width 64 1/2" (Measured across back of spoiler)	pass / fail	☐	
		Height: 5" Blade -or- 6.5" Blade (Per individual rule)	pass / fail	☐	
Spoiler centered on bumper cover seam		pass / fail	☐		
Spoiler blade mounted on front side of spoiler base		pass / fail	☐		
7- MANUFACTURER TAGS		Visible on inside of body panels	pass / fail	☐	
TEMPLATES	8- CENTERLINE TEMPLATES	Nose Centerline Template (Nose/Hood)	pass / fail	☐	
		Centerline Template (Roof/Deck Area)	pass / fail	☐	
	9- FENDER TEMPLATES	Left Template: located 21 3/4" from nose centerline	pass / fail	☐	
		Right Template: located 24 3/4" from nose centerline	pass / fail	☐	
	10- SIDE TO SIDE TEMPLATES	Roof Rear Side to Side Template (placed 90 degrees to roof)	pass / fail	☐	
		Roof Front Side to Side Template (placed 90 degrees to roof)	pass / fail	☐	
		Nose Width Template (placed on top of lower air dam)	pass / fail	☐	
11- HOOD PIN BAR	Rear Deck: Placed approx. 2" forward of the decklid hold-down recess	pass / fail	☐		
	(Placed along front edge of hood)	pass / fail	☐		
REFEREE	12- FRONT OVERHANG	47" maximum from center of nose to center of front spindles	pass / fail	☐	
	13- FRONT TREAD WIDTH	66" Maximum	pass / fail	☐	
	14- ROOF HEIGHT	Height range: 47" minimum / 48" maximum (measured 10" back from windshield)	pass / fail	☐	
	15- REAR-OF-DOOR HEIGHT	Minimum height: 33"	pass / fail	☐	
	16- WHEEL BASE	Stated range: 101" - 106"	pass / fail	☐	
	17- REAR TREAD WIDTH	66" Maximum	pass / fail	☐	
	18- QUARTER PANEL HEIGHT	Minimum height: 34 1/4" Maximum height: 34 1/2" (Measured at Quarter Panel, Bumper Cover and Deck Lid intersection)	pass / fail	☐	
	19- BUMPER COVER HEIGHT	Maximum height 34 7/8" at base of spoiler, on centerline	pass / fail	☐	
	20- REAR OVERHANG	47" maximum from center of rear axle to base of spoiler at center	pass / fail	☐	
	21- CENTERLINE DEVICE	The body centerline chain should be on centerline of the nose +/- 1" tolerance	pass / fail	☐	