



ABC NEXTGEN INSPECTION CHECKLIST

Driver Name	Date	Car #	Track
Tech Inspector (signed)	Team Representative (signed)		

		(Circle One)	Fix	Penalty
1- NOSE	Nose Screen- Mounted flush on lower air dam in the recess provided Minimum height from ground: 4" No holes allowed above the bumper line	pass / fail	<input type="checkbox"/>	_____
2- ROOF	Air intake Opening, Maximum: 2.5" x 20" Windshield Braces- Minimum 3 required Rear Window Braces- Minimum 3 required	pass / fail	<input type="checkbox"/>	_____
3- DOOR VENT WINDOWS	Must be 12" length along top of door 90 Degrees from top of door to A Pillar	pass / fail	<input type="checkbox"/>	_____
4- ROCKER PANEL HEIGHT	Minimum from ground to bottom of rocker: 4"	pass / fail	<input type="checkbox"/>	_____
5- WHEEL OPENING	7-1/2" Max from edge of rim to rear wheel opening	pass / fail	<input type="checkbox"/>	_____
6- SPOILER	Max Width 64 1/2" (Measured across back of spoiler) Height: 5" Blade -or- 6.5" Blade (Per individual rule) Spoiler centered on bumper cover seam Spoiler blade mounted on front side of spoiler base	pass / fail	<input type="checkbox"/>	_____
7- MANUFACTURER TAGS	Visible on inside of body panels	pass / fail	<input type="checkbox"/>	_____
		(Circle One)	Fix	Penalty
8- CENTERLINE TEMPLATES	Nose Centerline Template (Nose/Hood) Centerline Template (Roof/Deck Area)	pass / fail	<input type="checkbox"/>	_____
9- FENDER TEMPLATES	Left Template: located 21 3/4" from nose centerline Right Template: located 24 3/4" from nose centerline	pass / fail	<input type="checkbox"/>	_____
10- SIDE TO SIDE TEMPLATES	Roof Rear Side to Side Template (placed 90 degrees to roof) Roof Front Side to Side Template (placed 90 degrees to roof) Nose Width Template (placed on top of lower air dam) Rear Deck: Placed approx. 2" forward of the decklid hold-down recess (Placed along front edge of hood)	pass / fail	<input type="checkbox"/>	_____
11- HOOD PIN BAR		pass / fail	<input type="checkbox"/>	_____
		(Circle One)	Fix	Penalty
12- FRONT OVERHANG	47" maximum from center of nose to center of front spindles	pass / fail	<input type="checkbox"/>	_____
13- FRONT TREAD WIDTH	66" Maximum	pass / fail	<input type="checkbox"/>	_____
14- ROOF HEIGHT	Height range: 47" minimum / 48" maximum (measured 10" back from windshield)	pass / fail	<input type="checkbox"/>	_____
15- REAR-OF-DOOR HEIGHT	Minimum height: 33"	pass / fail	<input type="checkbox"/>	_____
16- WHEEL BASE	Stated range: 101" - 106"	pass / fail	<input type="checkbox"/>	_____
17- REAR TREAD WIDTH	66" Maximum	pass / fail	<input type="checkbox"/>	_____
18- QUARTER PANEL HEIGHT	Minimum height: 34 1/4" Maximum height: 34 1/2" (Measured at Quarter Panel, Bumper Cover and Deck Lid intersection)	pass / fail	<input type="checkbox"/>	_____
19- BUMPER COVER HEIGHT	Maximum height 34 7/8" at base of spoiler, on centerline	pass / fail	<input type="checkbox"/>	_____
20- REAR OVERHANG	47" maximum from center of rear axle to base of spoiler at center	pass / fail	<input type="checkbox"/>	_____
21- CENTERLINE DEVICE	The body centerline chain should be on centerline of the nose +/- 1" tolerance	pass / fail	<input type="checkbox"/>	_____

BODY REQUIREMENTS

TEMPLATES

REFEREE