



ORIGINAL ABC BODY INSPECTION CHECKLIST

Driver Name	Date	Car #	Track
Tech Inspector (signed)	Team Representative (signed)		

		(Circle One)	Fix	Penalty
1- NOSE	Nose Side Flap Height: Minimum 11.5" Minimum from ground to bottom of nose: 4" Minimum from bottom of nose to hood seam: 20" Nose Screen- Mounted flush on lower air dam in the recess provided No holes allowed above the bumper line	<i>pass / fail</i>	<input type="checkbox"/>	
2- COWL PANEL	Mandatory on car, ABC approved cowl panel Air intake Opening, Maximum: 2.5" x 20"	<i>pass / fail</i> <i>pass / fail</i>	<input type="checkbox"/> <input type="checkbox"/>	
3- VENT WINDOWS	Must be 12" length along top of door 90 Degrees from top of door to A Pillar	<i>pass / fail</i> <i>pass / fail</i>	<input type="checkbox"/> <input type="checkbox"/>	
4- WINDOW BRACES	Front- 3 required 1/8" thick x 1" wide Rear- 3 required 1/8" thick x 1" wide	<i>pass / fail</i> <i>pass / fail</i>	<input type="checkbox"/> <input type="checkbox"/>	
5- ROCKER PANEL HEIGHT	Minimum from ground to bottom of rocker: 4"	<i>pass / fail</i>	<input type="checkbox"/>	
6- WHEEL OPENING	7 1/2" Max from edge of rim to rear of all wheel openings	<i>pass / fail</i>	<input type="checkbox"/>	
7- MANUFACTURER TAGS	Visible on inside of each body panel	<i>pass / fail</i>	<input type="checkbox"/>	

		(Circle One)	Fix	Penalty
8- CENTERLINE TEMPLATES	Nose/Hood Template Roof Template	<i>pass / fail</i> <i>pass / fail</i>	<input type="checkbox"/> <input type="checkbox"/>	
9- FENDER TEMPLATES	Left: Measured on ground, 23 7/8" from centerline of nose Right: Measured on ground, 26 1/2" from centerline of nose	<i>pass / fail</i> <i>pass / fail</i>	<input type="checkbox"/> <input type="checkbox"/>	
10- SIDE TO SIDE TEMPLATES	Rear Roof Side to Side: Placed at back of roof (90 degrees to roof) Front Roof Side to Side: Placed at leading edge of roof (90 degrees to roof) Horizontal Nose (Horseshoe): Placed approx. 1" above top of nose screen Rear Deck: Placed approx. 2" forward of the decklid hold-down recess	<i>pass / fail</i> <i>pass / fail</i> <i>pass / fail</i> <i>pass / fail</i>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	

		(Circle One)	Fix	Penalty
12- FRONT OVERHANG	46" max. from center of nose from center of front spindles	<i>pass / fail</i>	<input type="checkbox"/>	
13- FRONT TREAD WIDTH	Recommended Max: 66"	<i>pass / fail</i>	<input type="checkbox"/>	
14- ROOF HEIGHT	Min Height: 47" - Max Height: 48" (at 10" back from windshield)	<i>pass / fail</i>	<input type="checkbox"/>	
15- REAR-OF-DOOR HEIGHT	Minimum Height: 33.0"	<i>pass / fail</i>	<input type="checkbox"/>	
16- WHEEL BASE	Stated Range: 101" - 106"	<i>pass / fail</i>	<input type="checkbox"/>	
17- REAR TREAD WIDTH	Recommended Max: 66"	<i>pass / fail</i>	<input type="checkbox"/>	
18- QUARTER PANEL HEIGHT	At Quarter Panel, Bumper Cover and Deck Lid intersection Stated Height Range: 34.25" to 34.5"	<i>pass / fail</i>	<input type="checkbox"/>	
19- BUMPER COVER HEIGHT	Top Height- 34 7/8" Max. at base of spoiler, on centerline	<i>pass / fail</i>	<input type="checkbox"/>	
20- REAR OVERHANG	47" max. from center of rear axle to base of spoiler at center	<i>pass / fail</i>	<input type="checkbox"/>	
21- CENTERLINE DEVICE	The body centerline chain should be on centerline of the nose +/- 1" tolerance	<i>pass / fail</i>	<input type="checkbox"/>	